

SECTION VIEW

RESIN BOUND AGGREGATE SYSTEM


GEOPAVEX IS A COLD TWO-PART POLYURETHANE RESIN BOUND AGGREGATE PAVING SYSTEM. THE POLYURETHANE RESIN BASE BONDS NATURAL AGGREGATES OR RECYCLED MATERIAL TO CREATE PERMEABLE, FLEXIBLE, AND LONG-LASTING SURFACES THAT OFFER LOW CARE MAINTENANCE.

GENERAL SPECIFICATIONS:

1. WARRANTY REQUIRES APPLICATION IS COMPLETED BY A TRAINED AND CERTIFIED APPLICATOR
2. GEOPAVEX IS APPLIED TO CLEAN DRY SURFACES. PLEASE FOLLOW MANUFACTURER INSTALLATION INSTRUCTIONS.
3. CLEAN AND FIRMLY COMPACT THE SOIL SUB BASE IN THE AREA TO BE PAVED, INSTALL ANY REQUIRED EDGING, AND PLACE GEOTEXTILE FABRIC TO KEEP SOIL FROM MIGRATING UPWARD.
4. ADD CLEAN CRUSHED AGGREGATE BASE TO A RECOMMENDED 2- 4 INCHES OF 3/4" CLEAN STONE WITHOUT FINES, LEAVING A MINIMUM OF ONE INCH (1") BELOW THE FINISHED GRADE FOR RESIN PAVING. LEVEL AND COMPACT THE BASE AGGREGATE.
5. MIX AND INSTALL GEOPAVEX PER THE MANUFACTURERS SPECIFICATIONS.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CompleteStreetsUSA.com



GEOPAVEX

RESIN BOUND AGGREGATE INSTALLATION