



SECTION VIEW

RESIN BOUND VEHICULAR BASE BUILD UP

POLYURETHANE RESIN PAVING IS A COLD TWO-PART POLYURETHANE RESIN PAVING SYSTEM. THE POLYURETHANE RESIN BASE BONDS NATURAL AGGREGATES OR RECYCLED MATERIAL TO CREATE PERMEABLE, FLEXIBLE, AND LONG-LASTING SURFACES.

GENERAL SPECIFICATIONS:

1. WARRANTY REQUIRES APPLICATION IS COMPLETED BY A TRAINED AND CERTIFIED APPLICATOR
2. GEOBOUNDX IS APPLIED TO CLEAN DRY SURFACES. PLEASE FOLLOW MANUFACTURER INSTALLATION INSTRUCTIONS FOR THESE COMPONENTS.
3. COMPACT AN APPLICABLE SUB-BASE IN THE AREA TO BE PAVED, AND PLACE GEOTEXTILE FABRIC TO KEEP SOIL FROM MIGRATING UPWARD.
4. INSTALL GROUND STABILIZATION MAT AND FILL WITH 3/8 " TO 1/2"
5. MIX AND INSTALL GEOBOUNDX PER THE MANUFACTURERS SPECIFICATIONS.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CompleteStreetsUSA.com

GEOBOUNDX

VEHICULAR INSTALLATION